



# DYNA GUARD 95X

## RUST PREVENTION / INHIBITOR

UPDATED: 14-September-2015

### GENERAL DESCRIPTION

**DYNA GUARD 95X** is a liquid material designed to give corrosion resistance on all metals.

**DYNA GUARD 95X** is very economical and simple to operate.

**DYNA GUARD 95X** may be added to cleaners the last stage of the phosphate line or in its own tank to enhance corrosion protection.

**DYNA GUARD 95X** can be operated in a mild steel tank.

### OPERATING INSTRUCTIONS

**DYNA GUARD 95X** will yield optimum results if operated within the following ranges:

Concentration: 1 to 20% by volume

Time: 60 to 120 seconds

Temperature: Room temperature

### MAINTENANCE

Fill the tanks 2/3's with cold water and agitate, as you add the calculated amount of **DYNA GUARD 95X** slowly into the tank. Then fill the tank with water to the required operating level. You may use the same instructions when adding **DYNA GUARD 95X** to cleaners.

### PACKAGING

**DYNA GUARD 95X** is shipped in 5 gallon pails and 55 gallon drums.

***NOTE:** To the best of our knowledge the information given in this data sheet is true and accurate. However, since the application of the products described herein is beyond our control, both the products and the information are offered without guarantee as to their use and nothing shall be taken as a recommendation to use any product in violation of any patent rights.*

DYNA TECH CHEMICAL SPECIALTIES, INC. ■ P. O. Box 34 ■ COLGATE, WI 53017

Phone: 262.646.7600 ■ Fax: 262.820.9176

Website: [www.dynatech.us](http://www.dynatech.us)